

ECOFLOW DELTA MAX PORTABLE POWER STATION (2000)

SPECIFICATIONS

Net Weight

Approx. 48 lbs (22 kg)

Dimension

19.6 x 9.5 x 12 in (49.7 x 24.2 x 30.5 cm)

Charge Temperature

32 to 113°F (0 to 45°C)

Discharge Temperature

-4 to 113°F (-20 to 45°C)

Warranty

24 months

Charge Method

AC Wall Outlet, 12V Car Adaptor, Solar Panel, Smart Generator, Smart Extra Battery

Full Recharge Time

1.6 Hours (AC) 21 Hours (12V Car Charger) 5.6-11.2 Hours (Using 4x 110W Solar Panels) 4.2-8.4 Hours (Using 4x 160W Solar Panels) 3.2-6.3 Hours (Using 2x 400W Solar Panels)

Capacity

2016Wh

Cell Chemistry

NCM

Cycle life

800 cycles to 80%+ capacity

Management Systems

BMS, Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Overcurrent Protection

Testing and Certification

CE WEEE CTP RCM KC

AC Charge Input (Power)

X-Stream charge (2000W max)

AC Charge Input (Voltage and Amperage)

220-240V~50Hz/60Hz, 10A



Solar Charge Input

11-100V 13A Max, 800W max

Car Charge Input

Supports 12V/24V Battery, Default 8A

AC Output (x4)

Pure Sine Wave, 2400W total (surge 4600W), 230V~ (50Hz/60Hz)

Max Device(s) Power Supported by X-Boost

3000W

USB-A Output (x2)

5V 2.4A, 12W max, per port

USB-A Fast Charge (x2)

5V/2.4A, 9V/2A, 12V/1.5A, 18W Max

USB-C Output (x2)

5/9/12/15/20V 5A, 100W max

Car Charger Output (x1)

12.6V/10A, 126W max

DC5521 Output (x2)

12.6V/3A, per port

Smart Extra Battery

Supports up to 2 DELTA Max Smart Extra Batteries (sold separately)

Smart Generator

Supported (sold separately)

Wi-Fi

Supported

GRIDX
metering and control