

# INFRARED ZOOM SPOTLIGHT IR10



## TECHNICAL PARAMETERS

### Model

IR10

### Version

See through rain/haze IR fill-in light(940nm)

### Electrical Interface

DJI SkyPort V2.0

### Size

186\*128\*158mm

### Weight

800±5g

### Power

≤40W

### Out Light Power

12±0.5W

### FOV

0.56°-45

### Luminous Wavelength

940nm

### Effective Distance

≥1000m

### Laser Safety Distance

≥90m

### Individual Control Angle

Pitch -125°~+40°

Horizontal ±320°

### IR10 Mount

Pitch -125°~+40°

### No.1 head port + DJIH20T

Horizontal -25°~+45°

### IR10 mount

Pitch -125°~+40°

### No. 2 head port + DJIH20T

Horizontal 15°~+12°

### IR10 mount

Pitch -125°~+40°

### No.1 head port + DJI H20

Horizontal ±45°

### IR10 mount

Pitch -125°~+40°

### No.2 head port + DJI H20

Horizontal ±45°

### Working temperature

-20°C~+50°C

## IR LASER FILL-IN LIGHT FOR STEALTH SURVEILLANCE

- Fiber laser generator Invisible by human eye
- Rated power up to 12W
- Rain and Smoke Haze see through
- Effective distance over 1000 meter

## IMAGING OPTIC WITHSHELL PROTECTION

- Imaging optic lens group
- Sharp and clear light fill-in
- Support starting at -35 degree centigrade
- Water/dust proof

## GIMBAL MOVEMENT EASY CONTROL

- Integrated smart chip
- Self-checking power supply condition and lamp board temperature
- Over discharge and over voltage can be independent power off
- Protection of power safety

## LINEAR ZOOM FLEXIBLE ADJUSTABLE LIGHT

- 70X zoom
- Precisely tracking
- Linear dimming adjustable
- Flexible control of brightness

**GRIDX**  
metering and control